

Technical Data Sheet nr. 529

AFRICA

Decorative architectural trowel-on coating, with stunning metallic patterns.

The **AFRICA** collection consists of a water-based finishing top coat with metallic pigments, available as a silver or gold base. The effects achieved with this product remind of ancient tissues and are perfectly suitable for decoration of interior walls in classical and modern environments. **AFRICA** is odourless, completely atoxic and water-based. **AFRICA** is a new product, which allows for highly prestigious quality results.

SUBSTRATE PREPARATION:

- Substrates must be perfectly dry and dust-free. A sealing coat of **NOVAPRIMER** (acrylic primer) diluted with 50-80% of water, depending on substrate absorption, is usually recommended.
- Wood and iron surfaces must be sealed with an adequate primer.

APPLICATION PROCEDURE

1. Apply one coat of **NOVAPRIMER**, acrylic primer with quartz powders, diluted with 50-80% of water, in a colour similar to the Dune shade.
2. Apply the first coat of **AFRICA** with short-piled roller, diluted with 20% of water.
3. On the dried surface apply the second coat of **AFRICA** diluted with roughly 10% of water with short-piled roller and decorate immediately with inox trowel, moving the same in circular movements. As alternative, apply directly with no dilution with the inox trowel and then work into it as above.

Any other tool, according to the professional taste can be used in order to create personal effects.

In case of applications in public areas a further protection with DUNE CLEAR COAT is strongly recommended. (see technical data sheet).

YIELD:

AFRICA: from 0,100 to 0,300lt/mq, according to the number of coats.

SPECIFIC WEIGHT:

1,07 kg/dm³



PACKAGING AND SHELF-LIFE

2,5lt and 1lt pails. The packaged product, if stored at temperatures between +5 and 35°C, is guaranteed for 12 months.

COLOUR RANGE

Colours of the colour card "AFRICA".