

Technical Data Sheet nr. 532

SWAHILI SILVER AND GOLD

Textured metallic decorative finish for interiors

The **SWAHILI** collection consists of a water-based finishing top coat with metallic pigments, available as a silver or gold base. The effects achieved with this product remind of ancient fabrics and are perfectly suitable for decoration of interior walls in classical and modern environments. **SWAHILI** is odourless, completely a-toxic and water-based. **SWAHILI** is a totally new concept of decoration, which guarantees quality results.

SWAHILI Silver and Gold are neutral bases, to tint with Mixcolor by Novacolor® tinting system or manually with universal pigments.

SUBSTRATE PREPARATION:

Substrates must be perfectly dry and dust-free.

- A sealing coat of **NOVAPRIMER** (acrylic primer) diluted with 50-80% of water, depending on substrate absorption, is usually recommended.
- Wood and iron surfaces must be sealed with an adequate primer.

SWAHILI APPLICATION PROCEDURE

- Apply two coats of **NOVALUX E** top quality paint for interiors and exteriors, tinted in a similar shade as Swahili.
- Apply **SWAHILI** in one coat, diluted with a maximum of 5% of clean water, with the “**brush for Swahili**”, working in small portions of wall.
- If required, in order to increase scrub resistance, protect with one or more coat of **CLEAR COAT**, applied with a short pile roller.

ALTERNATIVELY

- Apply two coats of **NOVALUX E** white, top quality paint for interiors and exteriors.
- Apply **SWAHILI** in two coats, diluted, if needed, with a maximum of 5% of clean water, with the “**brush for Swahili**”, working in small portions of wall. The second coat will be slightly more diluted.
- If required, in order to increase scrub resistance, protect with one or more coat of **CLEAR COAT**, applied with short pile roller.

YIELD:

from 0,150 to 0,300lt/mq

SPECIFIC WEIGHT:

SWAHILI SILVER: 1,23 kg /dm³

SWAHILI GOLD: 1,23 kg /dm³

PACKAGING AND SHELF-LIFE

5lt and 1lt pails.

The packaged product, if stored at temperatures between +5 and 35°C, is guaranteed for 12 months.

COLOUR RANGE

Silver and Gold Base as per Swahili colour card.

SPECIFICATIONS:

Application of decorative water-based coating with acrylic copolymers, selected metallic pigments, and special additives, manufactured by Novacolor, Forlì.

The product will be applied with a brush in one coat, diluted with a maximum of 5% of clean water, on a substrate previously treated with NOVAPRIMER, then prepared with NOVALUX E top quality paint for interiors and exteriors, tinted in a similar shade as Swahili.

Alternatively it will be applied with a brush in two coats, diluted with a 5%-10% of clean water, on a substrate previously treated with NOVAPRIMER, then prepared with NOVALUX E white, top quality paint for interiors and exteriors, working in small portions of wall.

If required, in order to increase scrub resistance, protect with one or more coats of **CLEAR COAT**, applied with short pile roller.

Exclusive of scaffolding, inclusive of flooring, frames and plant protection.

WARNING:

Dispose of the empty packaging and remaining material in compliance with local laws.